

# SAFETY DATA SHEET

SEALANT

Page: 1

Compilation date: 01/02/2016

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** SEALANT

**Product code:** PMST500P1

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Car cleaning and maintenance solution

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Power Maxed  
Unit 30  
Bidavon Industrial Estate  
Bidford-Upon-Avon  
Warwickshire  
B50 4JN  
United Kingdom

**Tel:** +44 (0) 1789 330 668

**Email:** info@powermaxed.com

### 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1789 330 668

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CHIP:** Xi: R36; -: R67

**Classification under CLP:** Eye Irrit. 2: H319; STOT SE 3: H336

**Most important adverse effects:** Irritating to eyes. Vapours may cause drowsiness and dizziness.

### 2.2. Label elements

#### Label elements under CLP:

**Hazard statements:** H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.

**Signal words:** Warning

**Hazard pictograms:** GHS07: Exclamation mark



**Precautionary statements:** P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

[cont...]

# SAFETY DATA SHEET

## SEALANT

Page: 2

P271: Use only outdoors or in a well-ventilated area.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor if you feel unwell.

### Label elements under CHIP:

**Hazard symbols:** Irritant.



**Risk phrases:** R36: Irritating to eyes.

R67: Vapours may cause drowsiness and dizziness.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

PROPAN-2-OL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-661-7	67-63-0	F: R11; Xi: R36; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

[cont...]

# SAFETY DATA SHEET

SEALANT

Page: 3

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. If outside keep bystanders upwind and away from danger point.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** See section 7 for information on safe handling. See Section 8 for information on personal protective equipment. See section 13 for disposal information.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** It is recommended to store in original packaging

[cont...]

# SAFETY DATA SHEET

SEALANT

Page: 4

## 7.3. Specific end use(s)

Specific end use(s): Car cleaning and maintenance product

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**PROPAN-2-OL**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m <sup>3</sup>	1250 mg/m <sup>3</sup>	-	-

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Wear Nitrile Gloves of minimum thickness 0.5mm. Gloves should be replaced regularly or if any change in appearance is noticed. Ensure gloves are manufactured/tested in accordance with BS EN 374. Penetration times carried out according to EN 374 part III are not always practical, therefore max. wearing time of 50% of penetration time is recommended.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** An environmental assessment must be made to ensure compliance with local environmental legislation.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Solubility in water:** Miscible

**Viscosity:** Non-viscous

**Flash point°C:** >61

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

[cont...]

# SAFETY DATA SHEET

SEALANT

Page: 5

## 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

## 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

#### Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

[cont...]

# SAFETY DATA SHEET

SEALANT

Page: 6

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** EU Legislation Regulation (EC) No 1907/2006 REACH. Regulation (EC) No 1272/2008 CLP.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

**Phrases used in s.2 and s.3:** H225: Highly flammable liquid and vapour.  
H319: Causes serious eye irritation.

[cont...]

# SAFETY DATA SHEET

## SEALANT

Page: 7

H336: May cause drowsiness or dizziness.

R11: Highly flammable.

R36: Irritating to eyes.

R67: Vapours may cause drowsiness and dizziness.

**Legend to abbreviations:** PNEC = predicted no effect level  
DNEL = derived no effect level  
LD50 = median lethal dose  
LC50 = median lethal concentration  
EC50 = median effective concentration  
IC50 = median inhibitory concentration  
dw = dry weight  
bw = body weight  
cc = closed cup  
oc = open cup  
MUS = mouse  
GPG = guinea pig  
RBT = rabbit  
HAM = hamster  
HMN = human  
MAM = mammal  
PGN = pigeon  
IVN = intravenous  
SCU = subcutaneous  
SKN = skin  
DRM = dermal  
OCC = ocular/corneal  
PCP = physico-chemical properties

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.